

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A method of monitoring performance of distributed applications including the steps of:

a client computer originating a request of service for a server computer,

[[if]] responsive to the request of service [[meets]] meeting at least one predefined condition, enabling [[the]] measuring on the client computer of at least one performance parameter for a transaction corresponding to the request of service and updating inserting a correlation identifier in the request of service by inserting a correlation identifier,

transmitting the request of service to the server computer,

[[if]] responsive to the request of service transmitted to the server computer including an inserted ~~includes the~~ correlation identifier, enabling [[the]] measuring on the server computer of the at least one performance parameter for a sub-transaction originating from the request of service,

executing the sub-transaction,

associating the correlation identifier with the at least one performance parameter measured on the server computer, and

associating the correlation identifier with the at least one performance parameter measured on the client computer, wherein the step of enabling measuring on the client computer of the at least one performance parameter for the transaction corresponding to the request of service and inserting the correlation identifier in the request of service includes verifying whether an address of the server computer matches a predetermined pattern stored on the client computer.

2. (Currently amended) The method according to claim 1, wherein the step of originating the request of service is performed under the control of a first module running on the client computer, the method further including the step of intercepting the request of service by a second module running on the client computer, the step of enabling the measuring on the client computer of the at least one performance parameter for the transaction corresponding to the request of service and updating the request by inserting the correlation identifier [[if]] responsive to the request of service [[meets]] meeting the at least one predefined condition being performed under the control of the second module.

3. (Currently amended) The method according to claim 1, further including at least one recursive execution of the steps of:

the server computer originating at least one further request of service for at least one further server computer,

~~[[if]] responsive to the request of service including includes the correlation identifier, updating the at least one further request by inserting a further correlation identifier in the at least one further request of service,~~

transmitting each further request of service to [[the]] a corresponding further server computer,

~~[[if]] responsive to the further request of service including includes the further correlation identifier, enabling [[the]] measuring on the corresponding further server computer of the at least one performance parameter for a further sub-transaction originating from the further request of service,~~

executing the further sub-transaction, and

associating the further correlation identifier with the at least one performance parameter measured on the corresponding further server computer.

4. (Canceled)

5. (Currently amended) [[The]] A method of monitoring performance of distributed applications including the steps of:

a client computer originating a request of service for a server computer,

responsive to the request of service meeting at least one predefined condition, enabling measuring on the client computer of at least one performance parameter for a transaction corresponding to the request of service and inserting a correlation identifier in the request of service,

transmitting the request of service to the server computer,

responsive to the request of service transmitted to the server computer including an inserted correlation identifier, enabling measuring on the server computer of the at least one performance parameter for a sub-transaction originating from the request of service,

executing the sub-transaction,

associating the correlation identifier with the at least one performance parameter measured on the server computer, and

associating the correlation identifier with the at least one performance parameter measured on the client computer according to claim 4, wherein the step of originating the request of service includes:

downloading a document from the server computer,

displaying the document, and

selecting a link in the document,
and wherein the step of enabling ~~[[the]]~~ measuring of the at least one performance parameter for the transaction and ~~updating the request by~~ inserting the correlation identifier in the request of service ~~[[if]]~~ responsive to the request ~~[[meets]]~~ meeting the at least one predefined condition includes:
verifying whether a definition of the document includes at least one enabling identifier, wherein the step of verifying whether the definition of the document includes the at least one enabling identifier includes one of verifying whether the definition of the document includes a global enabling identifier for all transactions originating from the document, and verifying whether a definition of the selected link includes a local enabling identifier for transactions originating from the selected link.

6-15. (Canceled)